

FORM PTO-1390
(REV 12-29-99)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

JCH10 Rec'd PCT/PTO 21 MAR 2001
MOT-D2194

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/787601INTERNATIONAL APPLICATION NO.
PCT/US99/21874INTERNATIONAL FILING DATE
21 September 1999PRIORITY DATE CLAIMED
21 September 1998

TITLE OF INVENTION APPARATUS AND METHOD FOR MERGING VERTICAL BLANKING INTERVALS

APPLICANT(S) FOR DO/EO/US Anthony Cucinotta

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
International Publication with Search Report;
International Preliminary Examination Report;
Written Opinion; and
Reply to Written Opinion

09/787601

PCT/US99/21874

17. ☒ The following fees are submitted:**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :**

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO \$1,000.00

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO \$860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but
international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =**CALCULATIONS** PTO USE ONLY

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☒ 30
months from the earliest claimed priority date (37 CFR 1.492(e)).

| CLAIMS | NUMBER FILED | NUMBER EXTRA | RATE |
|--------------------|--------------|--------------|-----------|
| Total claims | 24 - 20 = | 4 | X \$18.00 |
| Independent claims | 3 - 3 = | 0 | X \$80.00 |

MULTIPLE DEPENDENT CLAIM(S) (if applicable)

TOTAL OF ABOVE CALCULATIONS =

Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement
must also be filed (Note 37 CFR 1.9, 1.27, 1.28).

SUBTOTAL =

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(f)).

TOTAL NATIONAL FEE =

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

TOTAL FEES ENCLOSED =

| | |
|---------------------------|----|
| Amount to be refunded: | \$ |
| charged: | \$ |

- a. ☒ A check in the amount of \$ 1062.00 to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
overpayment to Deposit Account No. 22-0493. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR
1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Volpe and Koenig, P.C.
Suite 400, One Penn Center
1617 John F. Kennedy Boulevard
Philadelphia, PA 19103

SIGNATURE

Gerald B. Halt, Jr., Esquire

NAME

37,633

REGISTRATION NUMBER

2/PRTS

09/787601

APPARATUS AND METHOD FOR MERGING VERTICAL BLANKING INTERVALS

BACKGROUND

This invention is related to cable television (CATV) and wireless transmission
5 systems. More particularly, the invention is related to an apparatus for merging
selected lines of at least two vertical blanking intervals (VBIs) for transmission over
the RF band which is typically reserved for a single VBI.

With the increasing array of services from CATV and wireless network
operators, it has become imperative for operators to offer more services in the same
10 amount of RF transmission bandwidth. Moreover, wireless pay television systems,
whether MMDS or conventional VHF/UHF television, are generally constrained to
far fewer channels than the conventional CATV systems with which they compete.
The challenge is offering more channels to subscribers within the spectrum
constraints imposed by government regulations.

15 For a typical television program, since the video portion of the program
occupies most of the available 6 MHz on an NTSC television channel, much of the
research toward maximizing the amount of bandwidth has been traditionally devoted
towards compressing and minimizing the amount of bandwidth the video
information occupies. Accordingly there exists a need for providing more channel
20 capacity within the same amount of transmission bandwidth while maintaining the
quality of the transmitted data.

Ancillary information services are typically transmitted using existing
television broadcast channels. The ancillary information is transmitted in the VBI

-2-

and decoded at a television in order to display the ancillary information along with the television picture. Ancillary information typically includes text, for example closed captioning or related program information. Since the ancillary information transmitted along the VBI does not typically utilize the entire bandwidth assigned to the VBI, it is desirable to merge several VBIs into the bandwidth allotted for a single VBI in order to minimize the overall bandwidth required for the television transmission.

United Kingdom Patent Application No. GB 2286321A discloses a method for data distribution comprising storing packets of data in a random access memory, storing transmission characteristics for each packet, reading the characteristics and transmitting each packet to an audience in accordance with the frequency and timing parameters set forth in the packets' particular transmission characteristics. However, this system does not have the capability of merging the information from several VBIs into the bandwidth allotted for a single VBI.

SUMMARY

It is therefore an object of the invention to provide a method and apparatus for merging VBIs into the bandwidth allotted for a single VBI.

This and other objects have been achieved by providing a method and an apparatus for merging VBIs. The VBIs are merged by sequentially writing selected VBIs of a field to a first memory, then writing selected VBIs of a second field to a second memory while reading VBIs from the first memory in a desired sequence.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram of the merging system according to the present invention; and

Figure 2 is a diagram VBIs from two services merged into a single VBI.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention will now be described in greater detail with reference to the drawings, wherein like numerals represent like elements throughout. The system **10** shown in **Figure 1** for merging VBIs is divided into two symmetric halves **20**, **60**. The first half **20** is connected to a first service which will be referred to as service A while the second half **60** is connected to a second service which will be referred to as service B. A field programable gate array (FPGA) **40** is connected to a microprocessor (not shown) and controls both halves **20**, **60**. The preferred FPGA **40** for this system is a QuickLogic QL3025-2 PQ208C. It should be understood however that other commercially available field programmable gate arrays or other control circuits having similar functionality may be utilized as a substitute for this component. The FPGA **40** is preferably controlled by a microprocessor on a Zilog Z8S180 circuit card. It should also be understood that other commercially available microprocessors serving similar FPGA control functions may be utilized as a substitute for this component.

The FPGA **40** is connected to an input multiplexer **24** which receives input data from service A at port **22**. The input multiplexer **24** has a first output **41**

connected to number 1 data bus and a second output 42 connected to number 2 data bus. Both number 1 data bus and number 2 data bus are bidirectional to allow data flow in both directions. Memory 26 is connected to number 1 data bus at 46 and is controlled by the FPGA 40. It should be understood that while the memories 26 and 30 are shown as static RAM, other suitable memory devices may be utilized for this application. An address bus 45 extends from the memory 26 to a first control multiplexer 28. The first control multiplexer 28 has a first input 52 connected to the FPGA 40 and an output port 54 also connected to the FPGA 40. Input 52 is connected to a corresponding input on control multiplexers 62, 63 in the second half 60. Likewise, output port 54 is also connected to corresponding outputs on control multiplexers 62, 63 in the second half 60. A directional signal from the FPGA 40 is connected to the control multiplexer 28 at I/O select port 44. Likewise, a second directional signal from the FPGA 40 is connected to the control multiplexer 32 at I/O select port 43.

The number 1 data bus also extends to an output multiplexer 34 at port 36. The output multiplexer is connected to the number 2 data bus at port 38. A second memory 30 is connected to the number 2 data bus at port 50 and to an address bus 49 at port 48. The address bus 49 extends to a second control multiplexer 32 having an I/O select port 56 being connected to the input 52 of the first control multiplexer 28. An output port 58 is connected to the output port 54 of the first control multiplexer 28. Both ports 56 and 58 are also connected to the FPGA 40 and to corresponding control multiplexers 62, 63 in the second half 60. An output data bus

59 extends from the output multiplexer 34 and is coupled to a complimentary output multiplexer 64 of the second half 60.

Operation of the system 10 will be described in greater detail with reference to Figures 1 and 2. Turning first to Figure 2, it should be understood that a pair of services each containing a series of VBI information stored along selected lines of a picture field are to be merged into a single VBI. For example, Figure 2 shows a sample merged VBI. It can be seen that selected lines from service A and selected lines from service B are assembled into selected locations in the merged VBI. It should also be understood that, while only part of the lines displayed for service A and part of the lines for service B have been selected for the merged VBI, the merged VBI could be sized accordingly to receive all the selected lines of service A and all the selected lines of service B as long as the merged VBI does not exceed a maximum size limitation of a given television picture field. Assume, for example, that the desired information to be transmitted from service A appears on lines 10-21 of service A. Assume also, that the desired VBI information of service B appears at lines 10-21. The merged VBI can contain some of the lines from each service as shown in Figure 2 or it may contain all of the lines 10-21 from each service. This control is achieved by programming the FPGA 40 using a microprocessor (not shown). Those reasonably skilled in the art would appreciate that while lines 10-21 have been selected in these services for transmitting data along the VBI, other lines could be selected for transmitting the same data.

Referring back to **Figure 1**, service A is sampled at a desirable sample rate, for example this system utilizes 909 samples per video line, however it should be understood that other sample rates may be selected based upon design requirements or preferences. Service A sample data **22** is fed into the input multiplexer **24**. The
5 FPGA **40** controls the input multiplexer **22** to send the sample data either to port **41** along number 1 data bus or port **42** along number 2 data bus. The FPGA **40** controls each memory **26**, **30** so that, while memory **26** is receiving data from the input multiplexer **22** along number 1 data bus (write cycle), memory **30** is being read from port **50** along the number 2 data bus (read cycle) and vice versa. Therefore, VBI
10 lines corresponding to a given field and sampled at a rate of 909 samples per line are written into memory **26** while a series of lines from the previous field having been stored in a similar fashion are being read from the memory **30**.

Each of the memories **26**, **30** are controlled through a respective control multiplexer **28**, **32**. The FPGA **40** sends input addresses along the input address bus through input **52** and address bus **45** to the memory **26** to indicate where each
15 consecutive sample for the series of VBI lines is to be stored. These addresses are preferably sequential addresses, however it should be understood that the FPGA **40** may be programmed to control the memory **26** so that samples are stored in a non-sequential manner. Data is read from the memory **26** in the following cycle along number 1 data bus. Data is read from the memory **26** according to addresses sent by
20 the FPGA **40** along the output address bus to output port **54**. The data is read out of the memory in a non-sequential order as directed by addresses sent from the FPGA

40 through output port 54 of the control multiplexer 28. For example, as shown in Figure 2, data written in from line 18 of service B could be read out at line 12 in the merged VBI. The FPGA 40 could optionally be programmed to send addresses to the memory 26 such that data is read out sequentially. The data in the form of sampled VBIs is read along number 1 data bus into port 36 of the output multiplexer 34 and on to the output data bus 59. It should be understood that during a first cycle, the number 2 data bus has data flowing from the input multiplexer 24 into the memory 30 and there is no data flowing into port 38 of the output multiplexer 34. During the next cycle, data is read from the memory 30. The output data bus therefore receives non-sequential VBI line data corresponding to a first field from memory 26 and then receives non-sequential VBI data from a second field from memory 30. It should be understood however that the FPGA 40 could be programmed to read data out in any order including a sequential order. This process is duplicated for service B in system half 60. The processes are synchronized so that when memory 26 is in a read cycle, memory 66 is also in a read cycle. Accordingly, when memory 30 is in a read cycle, memory 68 is also in a read cycle. The same applies to memories 26 and 66. Write cycles are similarly synchronized. The output data bus 59 therefore receives some line samples from output multiplexer 34 and some line samples from output multiplexer 64 to create the merged VBI shown in Figure 2. The FPGA 40 controls the selection of lines from each service. Therefore, for each line of the merged VBI, (Figure 1) the FPGA 40 selects the service and line number from data previously stored in the memories.

An advantage of this invention is that several services VBIs may be transmitted in a single VBI thus reducing the bandwidth necessary for transmission.

It will be understood by those reasonably skilled in the art that minor variations of the embodiment presented here are intended to be within the scope of the invention. For example, where reference is made to sampling or digitizing data, it should be appreciated that similar analog methods could be substituted. Other such minor variations are intended to be within the scope of the invention which is intended to be limited only by the appended claims.

5
SCANNED, # _____

-9-

What is claimed is:

1. A method for merging vertical blanking intervals comprising:
storing a plurality of lines of data from a first service in a first memory (26)
during a first write cycle;
storing a plurality of lines of data from a second service in a third memory
(66) during the first write cycle;
storing a second plurality of lines of data from the first service in a second
memory (30) during a second write cycle;
storing a second plurality of lines of data from the second service in a fourth
memory (68) during the second write cycle;
reading selected lines of the data in the second and fourth memories (30), (68)
during the first write cycle; and
reading selected lines of the data in the first and third memories (26), (66)
during the second write cycle.
2. The method of claim 1 wherein the memories (26), (30), (66), (68) are
controlled by a controller (40).
3. The method of claim 2 wherein the controller (40) sends memory addresses
to the memories (26), (30), (66), (68) during the write cycles to direct the data into
selected memory locations.

-10-

4. The method of claim 3 wherein data is selected and read from locations in each memory (26), (30), (66), (68) according to addresses sent from the controller (40).

5. An apparatus for merging video data comprising:

a controller (40);

first (26), second (30), third (66), and fourth (68) memories, responsive to said controller (40);

an input address bus (45), (49) connected between the controller (40) and the memories (26), (30), (66), (68);

an output address bus connected between the controller (40) and the memories (26), (30), (66), (68);

a first service input (22) connected to the first (26) and second (30) memories;

and

a second service input (65) connected to the third (66) and fourth (68) memories; and an output bus (59) connected to the first (26), second (30), third (66), and fourth (68) memories.

6. The apparatus according to claim 5 further comprising a plurality of control multiplexers (28), (32), (62), (63) operatively connected to the controller (40), each for controlling a respective one of the memories (26), (30), (66), (68).

-11-

7. The apparatus according to claim 5 wherein the controller (40) comprises a field programmable gate array.

8. The apparatus according to claim 5 further comprising an output data bus (59) connected to each of the memories (26), (30), (66), (68).

9. The apparatus according to claim 8 further comprising a first output multiplexer (34) operatively connected between the first (26) and second (30) memories.

10. The apparatus according to claim 9 further comprising a second output multiplexer (64) operatively connected to the first output multiplexer (34) and between the third (66) and fourth (68) memories.

11. The apparatus according to claim 8 further comprising a first input multiplexer (24) for directing data into the first (26) and second (30) memories.

12. The apparatus according to claim 11 further comprising a second input multiplexer for directing data into the third (66) and fourth (68) memories.

13. The apparatus of claim 5 wherein said controller (40) stores data in the first (26) and third (66) memories while selectively reading data from the second (30)

-12-

and fourth (68) memories during a first cycle, and stores data in the second (30) and fourth (68) memories while selectively reading data from the first (26) and third (66) memories during a second cycle.

14. The apparatus according to claim 13 further comprising a plurality of control multiplexers (28), (32), (62), (63) operatively connected to each other and each being connected to a respective one of the memories (26), (30), (66), (68).

15. The apparatus according to claim 14 wherein said plurality of control multiplexers (28), (32), (62), (63) controls data flow in to and out of its respective memory (26), (30), (66), (68).

16. The apparatus according to claim 15 wherein said first output multiplexer (34) directs data out of the first (26) and second (30) memories to a common data bus (59).

17. The apparatus according to claim 16 wherein said second output multiplexer (64) directs data out of the third (66) and fourth (68) memories to the common data bus (59).





FIGURE 1

FIG. 10-109, 109, 109, 109



Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

| | | |
|---|-------------------------------|-------------------|
| DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input type="checkbox"/> Declaration Submitted with Initial Filing OR <input checked="" type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required) | Attorney Docket Number | MOT-D2194 |
| | First Named Inventor | Anthony Cucinotta |
| | COMPLETE IF KNOWN | |
| | Application Number | 09/787,601 |
| | Filing Date | Not Yet Known |
| | Group Art Unit | Not Yet Known |
| | Examiner Name | Not Yet Known |

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

APPARATUS AND METHOD FOR MERGING VERTICAL BLANKING INTERVALS

the specification of which (Title of the Invention)

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) 09/21/1999 as United States Application Number or PCT International

Application Number PCT/US99/21874 and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

| Prior Foreign Application Number(s) | Country | Foreign Filing Date (MM/DD/YYYY) | Priority Not Claimed | Certified Copy Attached? | |
|-------------------------------------|---------|----------------------------------|--------------------------|--------------------------|--------------------------|
| | | | | YES | NO |
| | | | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

| Application Number(s) | Filing Date (MM/DD/YYYY) | <input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto. |
|-----------------------|--------------------------|--|
| 60/101,181 | 09/21/1998 | |

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → +

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

| U.S. Parent Application or PCT Parent Number | Parent Filing Date (MM/DD/YYYY) | Parent Patent Number (if applicable) |
|--|---------------------------------|--------------------------------------|
| PCT/US99/21874 | 09/21/1999 | |

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: ☒ Customer Number 24375 → Place Customer Number Bar Code Label here

OR ☐ Registered practitioner(s) name/registration number listed below

| Name | Registration Number | Name | Registration Number |
|---|---------------------|------|---------------------|
| Namely, the Attorneys of Volpe and Koenig, P.C. | | | |

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number 24375 OR ☐ Correspondence address below

| | | | | | |
|---------|---------------------------------|-----------|--|-----|--|
| Name | VOLPE AND KOENIG, P.C. DEPT MOT | | | | |
| Address | | | | | |
| Address | | | | | |
| City | | State | | ZIP | |
| Country | | Telephone | | Fax | |

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

| | | | | | |
|--|--------------------------------|---|-----------|---------|----------------------|
| Name of Sole or First Inventor: | | <input type="checkbox"/> A petition has been filed for this unsigned inventor | | | |
| Given Name (first and middle (if any)) | | Family Name or Surname | | | |
| <u>Anthony</u> | | <u>Cucinotta</u> | | | |
| Inventor's Signature | <u>Anthony Cucinotta</u> | | | Date | <u>JUNE 25, 2001</u> |
| Residence: City | <u>Flower Mound</u> | State | <u>TX</u> | Country | <u>USA</u> |
| Post Office Address | <u>1525 Latigo Hills Trail</u> | | | | |
| Post Office Address | | | | | |
| City | <u>Flower Mound</u> | State | <u>TX</u> | ZIP | <u>75022</u> |
| | | | | Country | <u>USA</u> |

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto